



BEST

Kenmore Elite® and Kenmore® ENERGY STAR® Qualified Gas Water Heaters

- Glass-lined steel tank with anode rods for corrosion protection
- Self-cleaning, cold water inlet tube...swirls incoming water to help prevent sediment buildup
- 2" Energy-efficient, CFC-free foam insulation
- Factory-installed temperature and pressure relief valve
- Meets or exceeds British Columbia efficiency standards

Kenmore Elite® High Efficiency Gas Water Heaters				<ul style="list-style-type: none"> • Pressurized Combustion Chamber - Requires 120 Volt, grounded power supply • Advanced Technology, Eye-Level, LCD Control for easy temperature adjustment and diagnostics • Electronic Ignition - No pilot flame when there is no call for heat - Powered anode rod 							
Item Number	Warranty Tank/Parts	Tank Capacity		Type Gas	Btu/Hr. Input	U.S. Gal./Hr. Recovery @ 90°F (50°C) Rise	Dimensions in Inches			Vent Size	Energy Factor
		U.S. Gal.	Imp. Gal.				Diameter	Vent Outlet Height	Jacket Height		
73280	12 yr. / 12 yr.	40	33	Natural	40,000	43	20"	62"	58.25"	3" or 4"	0.70
73281	12 yr. / 12 yr.	50	42	Natural	40,000	43	22"	61"	57.25"	3" or 4"	0.70

Kenmore® Flue Damper Gas Water Heaters				<ul style="list-style-type: none"> • Electronic Ignition - No pilot flame when there is no call for heat • Self-Diagnostic Electronic Gas Valve - Requires 120 Volt, grounded power supply • ENERGY STAR® Qualified 							
Item Number	Warranty Tank/Parts	Tank Capacity		Type Gas	Btu/Hr. Input	U.S. Gal./Hr. Recovery @ 90°F (50°C) Rise	Dimensions in Inches			Vent Size	Energy Factor
		U.S. Gal.	Imp. Gal.				Diameter	Vent Outlet Height	Jacket Height		
73220	12 yr. / 12 yr.	40 Short	33	Natural	40,000	41	22"	54"	47.75"	3" or 4"	0.67
73222	12 yr. / 12 yr.	50 Short	42	Natural	40,000	41	24"	55"	48.75"	3" or 4"	0.67
73290	9 yr. / 9 yr.	40 Short	33	Natural	40,000	41	22"	54"	47.75"	3" or 4"	0.67
73292	9 yr. / 9 yr.	50 Short	42	Natural	40,000	41	24"	55"	48.75"	3" or 4"	0.67

BETTER

Kenmore® Gas Water Heaters

- Glass-lined steel tank with two large anode rods for corrosion protection
- Self-cleaning, cold water inlet tube...swirls incoming water to help prevent sediment buildup
- Energy-efficient, CFC-free foam insulation
- Factory-installed temperature and pressure relief valve
- Meets or exceeds British Columbia efficiency standards

Conventional Gas Water Heaters				<ul style="list-style-type: none"> • Easy-to-light, Piezo ignition system • No Electric Power Supply Required 							
Item Number	Warranty Tank/Parts	Tank Capacity		Type Gas	Btu/Hr. Input	U.S. Gal./Hr. Recovery @ 90°F (50°C) Rise	Dimensions in Inches			Vent Size	Energy Factor
		U.S. Gal.	Imp. Gal.				Diameter	Vent Outlet Height	Jacket Height		
73930	12 yr. / 12 yr.	40 Tall	33	Natural	40,000	41	20"	62"	58.25"	3" or 4"	0.62
73931	12 yr. / 12 yr.	50 Tall	42	Natural	40,000	41	22"	61"	57.25"	3" or 4"	0.62
73911	9 yr. / 9 yr.	40 Tall	33	Natural	40,000	41	20"	62"	58.25"	3" or 4"	0.62
73912	9 yr. / 9 yr.	50 Tall	42	Natural	40,000	41	22"	61"	57.25"	3" or 4"	0.62
73910	9 yr. / 9 yr.	40 Short	33	Natural	40,000	41	22"	51.5"	47.75"	3" or 4"	0.62
73900	6 yr. / 6 yr.	40 Short	33	Natural	40,000	41	22"	51.5"	47.75"	3" or 4"	0.62

Power Vent Water Heaters

- Energy-saving, Hot Surface Ignition System...no standing pilot
- Uses PVC pipe for venting system
- No chimney required...Vents through outside wall or roof
- Requires 120-volt, grounded power supply
- Meets or exceeds British Columbia efficiency standards

Item Number	Warranty Tank/Parts	Tank Capacity		Type Gas	Btu/Hr. Input	U.S. Gal./Hr. Recovery @ 90°F (50°C) Rise	Dimensions in Inches			Vent Size	Energy Factor
		U.S. Gal.	Imp. Gal.				Diameter	Vent Outlet Height	Jacket Height		
73425	9 yr. / 6 yr.	50 Tall	42	Natural	40,000	44	20"	65"	56.75"	2", 3" or 4"	0.65
73426	9 yr. / 6 yr.	50 Tall	42	Natural	50,000	53	22"	65"	56.75"	2", 3" or 4"	0.65

GOOD

Kenmore® Gas Water Heaters

- Glass-lined steel tank with anode rod for corrosion protection
- Easy-to-light, Piezo ignition system
- Energy-efficient, CFC-free foam insulation
- Factory-installed temperature and pressure relief valve

Item Number	Warranty Tank/Parts	Tank Capacity		Type Gas	Btu/Hr. Input	U.S. Gal./Hr. Recovery @ 90°F (50°C) Rise	Dimensions in Inches			Vent Size	Energy Factor
		U.S. Gal.	Imp. Gal.				Diameter	Vent Outlet Height	Jacket Height		
73830	12 yr. / 12 yr.	40 Tall	33	Natural	50,000	51	20"	62.5"	58.25"	4"	0.59
73831	12 yr. / 12 yr.	50 Tall	42	Natural	50,000	51	22"	61.5"	57.25"	4"	0.58
73811	9 yr. / 9 yr.	40 Tall	33	Natural	40,000	41	18"	62"	58.25"	3" or 4"	0.59
73810	9 yr. / 9 yr.	40 Short	33	Natural	40,000	41	20"	51.5"	47.75"	3" or 4"	0.59
73616	9 yr. / 9 yr.	50 Short	45	Natural	45,000	46	24"	53.25"	48.75"	4"	0.58
73801	6 yr. / 6 yr.	40 Tall	33	Natural	40,000	41	18"	62"	58.25"	3" or 4"	0.59
73800	6 yr. / 6 yr.	40 Short	33	Natural	40,000	41	20"	51.5"	47.75"	3" or 4"	0.59

Dimensions and product specifications are subject to change without notice.

Gas water heaters shown are not certified for use in mobile homes.

All models shown comply with the latest efficiency requirements of NRCAN.

Item numbers shown in **Bold** meet or exceed British Columbia Energy Efficiency Requirements

Kenmorehot!

Electric Water Heaters - 2011



BEST

Kenmore® Electric Water Heaters - 12-Year Limited Warranty on tank and parts

- Glass-lined steel tank with two large anode rods for corrosion protection
- Self-cleaning RotoSwirl™ cold water inlet tube...swirls incoming water to help prevent sediment buildup
- Super Limeguard™, stainless steel heating elements
- 3" Energy-efficient, CFC-free foam insulation
- DUALWATT™ lower element...converts from 3800 watts to 5500 watts... for use with either 20 amp or 30 amp fuses or circuit breakers
- Factory-installed temperature and pressure relief valve
- Meet or exceed British Columbia efficiency standards

Item Number	Tank Capacity		Wattage at 240 Volts	Minimum Fuse Required	Minimum Wire Size	Recovery @ 90°F (50°C) Rise		Dimensions in Inches		Standby Watts Loss
	Litres	Imp. Gal.				Litres per Hr.	Imp. Gal. per Hr.	Diameter	Height	
73432	273	60.0	3800	20 amp	12 ga.	65.5	14.4	26"	62"	62
			5500	30 amp	10 ga.	94.8	20.9			
73433	170	37.5	3800	20 amp	12 ga.	65.5	14.4	24"	50"	49
			5500	30 amp	10 ga.	94.8	20.9			

BETTER

Kenmore® Electric Water Heaters - 9-Year Limited Warranty on tank and parts

- Glass-lined steel tank with two anode rods for corrosion protection
- Self-cleaning RotoSwirl™ cold water inlet tube...swirls incoming water to help prevent sediment buildup
- Limeguard™, zinc-coated, copper heating elements
- 2.5" Energy-efficient, CFC-free foam insulation
- DUALWATT™ lower element...converts from 3800 watts to 5500 watts... use with either 20 amp or 30 amp fuses or circuit breakers
- Factory-installed temperature and pressure relief valve
- Meet or exceed British Columbia efficiency standards

Item Number	Tank Capacity		Wattage at 240 Volts	Minimum Fuse Required	Minimum Wire Size	Recovery @ 90°F (50°C) Rise		Dimensions in Inches		Standby Watts Loss
	Litres	Imp. Gal.				Litres per Hr.	Imp. Gal. per Hr.	Diameter	Height	
73416	225	49.4	3800	20 amp	12 ga.	65.5	14.4	23"	61"	63
			5500	30 amp	10 ga.	94.8	20.9			
73417	273	60.0	3800	20 amp	12 ga.	65.5	14.4	25"	61.5"	70
			5500	30 amp	10 ga.	94.8	20.9			
73418	187	41.2	3000	15 amp	14 ga.	51.7	11.4	21.5"	61"	58
73419	187	41.2	3800	20 amp	12 ga.	65.5	14.4	21.5"	61"	59
			5500	30 amp	10 ga.	94.8	20.9			

GOOD

Kenmore® Electric Water Heaters - 6-Year Limited Warranty on tank and parts

- Glass-lined steel tank with anode rod for corrosion protection
- Two, zinc-coated, copper heating elements
- Energy-efficient, CFC-free foam insulation
- Factory-installed temperature and pressure relief valve
- Items shown in **BOLD** meet or exceed British Columbia efficiency standards

Item Number	Tank Capacity		Wattage at 240 Volts	Minimum Fuse Required	Minimum Wire Size	Recovery @ 90°F (50°C) Rise		Dimensions in Inches		Standby Watts Loss
	Litres	Imp. Gal.				Litres per Hr.	Imp. Gal. per Hr.	Diameter	Height	
73402	170	37.5	3000	15 amp	14 ga.	51.7	11.4	22"	48"	64
73403	273	60.0	4500	30 amp	10 ga.	77.6	17.1	24"	60.5"	78
73404	187	41.2	3000	15 amp	14 ga.	51.7	11.4	20.5"	60.25"	68

GOOD

Kenmore® Compact and Point-of-Use Water Heaters - 6-Year Limited Warranty on tank and parts

- Glass-lined steel tank with anode rod for corrosion protection
- Two, zinc-coated, copper heating elements
- Energy-efficient, CFC-free foam insulation
- Factory-installed temperature and pressure relief valve
- Items shown in **BOLD** meet or exceed British Columbia efficiency standards

Item Number	Tank Capacity		Element Wattage		Minimum Fuse Required	Minimum Wire Size	Recovery @ 90°F (50°C) Rise		Dimensions in Inches		Standby Watts Loss
	Litres	Imp. Gal.	120 V.	240 V.			Litres per Hr.	Imp. Gal. per Hr.	Diameter x Height		
73772	34	7.5	1500		15 amp	14 ga.	25.9	5.7	16" x 18.25"		N/A
73773	67	14.8	1500		15 amp	14 ga.	25.9	5.7	19" x 25.25"		43
73443	102	22.5		3000	15 amp	14 ga.	51.7	11.4	22" x 30"		47
73771*	9.5	2.0	1500		15 amp	14 ga.	25.9	5.7	11" x 14" x 16"		N/A

* Item 73771, Point-of-Use water heater, has a 6-year warranty on tank and a 1-year warranty on parts.

Dimensions and product specifications are subject to change without notice.

All models shown comply with the latest efficiency requirements of NRCAN.

Item Numbers shown in **BOLD** meet or exceed British Columbia Energy Efficiency Requirements